



Unit 1 Eco Business Park, Eco Way, Doncaster, DN7 4JJ
info@stonelux.co.uk • 01405 720281 • stonelux.co.uk

TECHNICAL DATA SHEET

BRICK TINIT

Stonelux Brick Tint is a high-quality tinting solution designed to enhance the appearance of masonry surfaces such as brick, stone, and mortar. It offers exceptional colour customisation possibilities while effectively permeating the substrate's pores, resulting in a stunning and long-lasting outcome that maintains its incredible appearance over time.

Whether you're revitalising an old structure or adding a touch of character to a new build, Stonelux Brick Tint delivers exceptional results. Suitable for interior and exterior use.

1. AVAILABILITY

Stonelux Brick Tint is available in 1 litre, 2.5 litre and 5 litre containers. Readily available in 12 common brick colours. Colours can be mixed to achieve alternative shades. Colour matching is also available.

2. FIELD OF APPLICATION

Stonelux Brick Tint is designed to permanently change the colour of masonry. Suitable for application onto porous brick, stone and mortar. Not suitable for non-porous and sealed surfaces.

Recommended Substrates

Brick, stone, mortar, concrete and other porous substrates.

3. PROPERTIES

Drying time: In normal drying conditions allow a minimum of 1 hour drying time between coats. Fully cured in 72 hours. Drying times may vary depending on temperature and humidity.

Coverage: Up to 20-25 meters squared per litre. Coverage will vary depending on the porosity of the substrate and the desired effect.

Limitations: Do not apply in rain, temperatures below 10°C, above 30°C or if exposure to these conditions or frost is likely during the curing time. Not suitable for non-porous surfaces. To check for porosity splash water onto the substrate, if the water is absorbed and the substrate remains wet, it is porous. If the water turns into beads and runs away, the surface is not porous.

4. PREPARATION

Ensure the substrate is clean, sound and dry, removing any existing flaking materials

5. APPLICATION INSTRUCTIONS

Stonelux Brick Tint should be applied using a natural bristled brush. We recommend a 2" brush for most bricks, and a 0.5" brush or smaller for mortar joints.

Mix well before and during use. Dip brush in tint and remove any excess to minimise risk of drips. Apply to the surface of the substrate as required.

Use caution when working around windows, doors or other areas where the tint may come into contact with surrounding surfaces.

If a deeper colour is required, wait for the tint to dry before applying a second coat.

If a lighter colour is required, prior to application add water to the tint at a maximum ratio of 50:50.

6. CLEANING

Clean equipment and brushes with water after use. Do not empty materials into drainage system.

7. STORAGE

Store in dry, cool conditions between 10°C and 30°C. If stored correctly and unopened the product will have a shelf life of at least 18 months.

8. SAFETY INSTRUCTIONS

See the Material Safety Data Sheet for further information.

FURTHER INFORMATION

If you require further information, please contact Stonelux Limited on 01405 720281.

Material Safety Data Sheet is available on request or by visiting www.stonelux.co.uk.

Care is taken to ensure the accuracy of the information provided in this Technical Data Sheet. However, Stonelux Limited is unable to guarantee any results due to a lack of control over the application techniques used or the conditions under which StoneLux products are applied.